

Dots

Design by Martín Azúa.

VIBIA

Reference

4665.

Application

Wall Lamps

Installation type

Surface

Description

The Dots indirect lamp is a compact, circular wall sconce that offers diffuse lighting effects. The luminaire features a concave form that reflects light off its lacquered surface like the glow of the moon at night. Available in four lacquered Chromatica colours.

Diffuser

Polycarbonate diffuser

Materials

Body: ABS

Driver box: Aluminum

Finish



4665-13 White Grey L1 (NCS S 1000-N)



4665-27 Brown L1 (NCS S 1505-Y50R)




4665-37 Terra Red (NCS S 4040-Y70R)



4665-47 Green L1 (NCS S 4005-G80Y)

Sketch



Electrical characteristics

1 x LED 5,75W 500mA



Total 5.8 W



Light source: 2700K CRI >90 500 lm 87 lm/W

Driver included: CC - Constant Current 500 mA 220~240V 50/60Hz

Physical characteristics

1 Box / 0.13 x 0.20 x 0.21 m. / Vol. 0.0054 m³ /

Gross weight 0.7 kg. / Net weight 0.4 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency : 22.72 lm/W

Coordinate system : CG

Total flux : 183.09 lm

Maximum value : 170.27 cd

Light position : C=90.00 G=20.00

Symmetry on the planes : Symmetrical planes

270-90



Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m



Certificates

